

SWIVEL JOINTS

SWIVEL JOINTS ALLOW FOR ADJUSTABLE SPRAY DIRECTION



APPLICATION

Industrial Washing Machines
Product Washing
Pre-treatment

FEATURES

Swivel Joints allow adjustable alignment of spray nozzles
Greater control over spray direction
From 40° to 70° adjustment

DESCRIPTION

Our range of swivel joints allow you to adjust the angle and direction of the spray nozzle used without expensive piping changes.

Using these swivel joints allows greater control of spray direction for precise coverage.

MATERIALS AVAILABLE

Stainless Steel
Brass

Swivel Joint Dimensions						
Part Number	A Inlet Pipe Conn. BSP or NPT	B Outlet Pipe Conn. BSP or NPT	C Outlet Length (mm)	D Hex Size (mm)	E Angle of Adjustment	Net Wt. (g)
1/4 x 1/4	1/4M	1/4F	44.5	38.1	70°	227
3/8 x 1/4	3/8M	1/4F	44.5	38.1	70°	227
3/8 x 3/8	3/8M	3/8F	44.5	38.1	55°	227
1/2 x 3/8	1/2M	3/8F	44.5	38.1	55°	227
1/2 x 1/2	1/2M	1/2F	61.9	38.1	60°	425
1/2 x 3/4	1/2M	3/4F	61.9	38.1	40°	425
3/4 x 1/2	3/4M	1/2F	61.9	38.1	60°	425
3/4 x 3/4	3/4M	3/4F	61.9	38.1	40°	425

